


65 Solid and stable

	LEGUAN 165
SWL for the entire working area	230 kg / 2 persons
Max. working height	16.40 m
Max. platform height	14.40 m
Max. outreach	7.85 m
Transport length	5.01 m
Platform dimensions W x L	1.33 x 0.75 m
Rotation of basket	90° (±45°)
Slewing	360°
Gradeability	35% (20°)
Outrigger spread working	3.78 x 3.83 m
Max. slope for outriggers	22% (I3°)
Weight with tracks / tyres	2530 kg/2530 kg
Power source	Kubota 14 hp diesel
	230 V / I I 0 V
Drive system: hydraulic	4WD
	Tracks
Drive speed max.	2,6 km/h (5,2 km/h*)



- · Robust three boom design
- **Direct hydraulic controls**
- **Active weight control**
- **Ground contact sensing** outrigger control
- **Telescopic boom**
- Negative jib boom (120 deg.)
- High platform capacity over whole working area
- **Excellent maneuverability next** to a wall, straight vertical lifting up to II m







Ylötie 10, FI-33470 Ylöjärvi, Finland Tel. +358 3 347 6400 Fax +358 3 347 6446 leguan@avanttecno.com

Leguan has a policy of continuing improvement, and retains the right to change specifications without notice. © 2016 LEGUAN Lifts Oy. All rights reserved.